

AM4113T5



The AM4113T5 with a high magnification of 500x reveals even the smallest details on all kinds of objects. This model also provides the possibility to calibrate the microscope for measurements.



USB 2.0



MEASUREMENT
FUNCTIONALITY



FIXED
~500x



MAGNIFICATION
LOCK



1.3 MEGAPIXEL
1280 x 1024



8 WHITE LEDs
SWITCHABLE



STANDARD
WORKING
DISTANCE

Additional Info

- Dino-Lite Range: Dino-Lite High Magnification
- Resolution: Medium (800x600 - 1.3 Megapixel)
- Magnification: High (above 400x)
- Interface: USB 2.0
- Working Distance: Standard
- Price Range (excl. VAT): €200,00 - €350,00
- Light/ LED type: White
- ESD Safe: No
- Polarizer: No
- Housing: Composite/plastic housing
- Special feature: No
- Dino-Lite Range: Dino-Lite High Magnification

- Light/ LED type: White
- Number of LEDs: 8
- LED on/off switchable: Yes
- Infrared filter: IR cut-filter >650 nm
- Diffuser available: No
- Emission filter: No
- Polarizer: No
- Magnification: 500x
- Macro zoom: No
- Working Distance: Standard
- Resolution: 1.3 Megapixel (1280x1024)
- Maximum Frame rate: 30 fps
- Interface: USB 2.0
- Housing material: Composite/ plastic housing
- Magnification lock: Yes
- Measurement: Yes
- Calibration: Yes
- Microtouch sensor: Yes
- ESD Safe: No
- Special feature: No
- Package contents: Microscope, Carry pouch, Software CD, Calibration target, User manual
- Price Range: €200,00 - €350,00

- **Details**

- Dino-Lite range: Dino-Lite High Magnification

- **Lighting**

- Light/ LED type: White
- Number of LEDs: 8
- LED on/off switchable: Yes
- Infrared filter: IR cut-filter >650 nm
- Diffuser available: No
- Emission filter: No
- Polarizer: No

- **Optics**

- Magnification: 500x
- Macro zoom: No
- Working distance: Standard
- Lens type: Glass with anti-reflection coating

- **Sensor**

- Sensor type: CMOS
- Resolution: 1.3 Megapixel (1280x1024)
- Maximum frame rate: 30 fps

• **Compatibility**

- Interface: USB 2.0
- Operating system: Windows XP, Vista, 7, 8 & 10, MacOS 10.9 and up
- Included software: DinoCapture 2.0 (Windows), DinoXscope (Mac OS)
- Supported image formats (Windows): BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX
- Supported video formats (Windows): WMV, FLV, SWF
- Supported image formats (MacOS): JPEG, PNG
- Supported video formats (MacOS): MOV
- Imaging standards: DirectShow, UVC

• **Housing**

- Housing material: Composite/ plastic housing
- Magnification lock: Yes
- Dimensions: 10.5cm (L) x 3.2cm (D)
- Weight: 105g
- Cable length: 1.8m

• **Features**

- Special feature: No
- Measurement: Yes
- Calibration: Yes
- Microtouch sensor: Yes
- ESD safe: No

• **Information**

- Package contents: Microscope, Carry pouch, Software CD, Calibration target, User manual
- Warranty information: 2 years European warranty
- Regulatory approval: CE, FCC, ROHS
- Price range: €200,00 - €350,00
- Working distance/ field of view/ depth of field:

Magnification Rate	Working Distance	Field of View(x)	Field of View(y)	Depth of Field
515	0.1	0.8	0.6	0.07
Listed values may differ slightly				Unit = mm

PDF generated on: 04-04-2019